

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification 7 :</b> C07C 233/02, C09D 5/16, C07C 331/24, 265/08	<b>A1</b>	<b>(11) International Publication Number:</b> WO 00/55117 <b>(43) International Publication Date:</b> 21 September 2000 (21.09.00) <b>not. s.</b>
<b>(21) International Application Number:</b> PCT/EP00/02118 <b>(22) International Filing Date:</b> 10 March 2000 (10.03.00) <b>(30) Priority Data:</b> 99105349.7 16 March 1999 (16.03.99) EP <b>(71) Applicants (for all designated States except US):</b> BAYER AKTIENGESELLSCHAFT [DE/DE]; D-51368 Leverkusen (DE). UNIVERSITE LIBRE DE BRUXELLES [BE/BE]; CP 160/06 Avenue Roosevelt, B-1050 Bruxelles (BE). NEDERLANDSE ORGANISATIE VOOR TOEGEPAST, NATUURWETENSCHAPPELIJK ONDERZOEK [NL/NL]; Postbus 6235, NL-5600 HE Eindhoven (NL). SIGMA COATINGS B.V. [NL/NL]; Amsterdamseweg 14, NL-1422 AD Uithoorn (NL). <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> KUNISCH, Franz [DE/DE]; Am Erlenfeld 3, D-51519 Odenthal (DE). KUGLER, Martin [DE/DE]; Am Kloster 47, D-42799 Leichlingen (DE). BRAEKMAN, Jean, Claude [BE/BE]; 7 Avenue, Sainte Therese, B-1640 Rhode Saint Genese (BE). PLEHIERS, Mark [BE/BE]; 21 Rue Le Corregge, B-1000 Bruxelles (BE). FERRARI, Gabriele, M. [NL/NL]; TNO Institute of Industrial Technology, De Wielen 6, NL-5612		<b>AV Eindhoven (NL). VOS, Marcel [NL/NL]; Hoofdweg 58, NL-1275 AD Huizen (NL).</b> <b>(74) Common Representative:</b> BAYER AKTIENGESELLSCHAFT; D-51368 Leverkusen (DE). <b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> ROSIN AMINE ANTI-FOULING AGENTS		
<b>(57) Abstract</b>		
<p>The invention relates to new and known compounds as well as methods for preventing the attachment of aquatic organisms to surfaces which are submerged for extensive periods of time in water. More particularly, this invention relates to the protection of submerged surfaces with <u>new</u> isonitrile, formamide, isocyanate and isothiocyanate anti-fouling agents.</p>		
<p style="text-align: right;">"Express Mail" mailing label number <u>ET146894121US</u> Date of Deposit <u>September 6, 2001</u></p> <p>I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, D.C. 20231</p> <p style="text-align: center;">Donna J. Veatch (Name of person mailing paper or fee)  (Signature of person mailing paper or fee)</p> <p style="text-align: left; font-size: 2em;">Le</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

**Rosin Amine Anti-Fouling Agents**

**Field of invention**

5 The invention relates to new and known compounds as well as methods for preventing the attachment of aquatic organisms to surfaces which are submerged for extensive periods of time in water. More particularly, this invention relates to the protection of submerged surfaces with new isonitrile, formamide, isocyanate and isothiocyanate anti-fouling agents.

10

**Background of the invention**

The ever recurring growth of fouling organisms on underwater structures such as ships, docks, piers, pilings, fishnets, heat exchangers, dams, piping structures, intake screens, cooling towers and the like is a costly and hazardous problem in both marine and freshwater endeavors. The presence of fouling organisms such as barnacles, zebra mussels, algae, diatoms, hydroids, bryozoa, ascidians, tubeworms, Asiatic clams and the like causes economic damage in various ways: for example, attachment to the hulls of ships reduces fuel efficiency and causes loss of profitable sailing time because of the need to clean the hulls. Similarly, the attachment of these organisms to cooling water equipment decreases heat conductivity which eventually reduces or block the cooling power of the equipment and drives up cost.

20

A variety of agents useful for controlling fouling organisms in fresh water or sea water have been used to prevent the attachment and overgrowth of these organisms.

25

A common method of controlling the presence or attachment of fouling organisms is to coat or permeate the underwater structure with a composition which comprises mixtures of toxic compounds such as tri-n-butyl tin or copper compounds. Anti-fouling agents in the form of a paint can contain up to 60% by weight of the active ingredients and can be used to paint surfaces such as the hull of ships. The paint prevents attachment and growth of fouling organisms by continuously releasing anti-fouling agents underwater. The disadvantage of many of the present anti-fouling

30

agents is that they are persistent in the environment, are often acutely toxic and degrade too slowly in aquatic environments and are, therefore, ecologically harmful. Hazardous anti-fouling agents can eventually bioaccumulate and enter the food chain and therefore represent a threat to marine and human life.

5

For example, it is well established that heavy metal compounds, especially organotin compounds that are widely used as anti-fouling agents, accumulate in mussels.

10

It is an object of this invention to provide an environmentally and ecologically sound method of combatting or controlling marine and freshwater fouling organisms.

It is another object of this invention to provide an effective method for protecting aquatic structures against fouling by marine or freshwater fouling organisms.


15

It is a further object of this invention to provide antifoulant compositions which comprises certain derivatives of rosin compounds as the active agents.


#### Summary of the Invention

20


The present invention provides new and known compounds and a method to prevent settlement on surfaces by marine or freshwater fouling organism which comprises contacting said organism or the locus thereof with an anti-fouling-effective amount of at least one compound of formula I1-I13




I1




I2




I3




I4




I5




I6




I7




I8




I9



I10



I11



I13

formula I1 - I13

wherein

$R^1$  represents  $NR^2R^3$  wherein

**R<sup>2</sup>** represents a hydrogen atom, C1 - C8-alkyl and

$R^3$  represents  $C=OR^4$  wherein

$R^4$  represents a hydrogen atom or one of the groups  $OR^5$  or  $NHR^5$  wherein

**R<sup>5</sup> designates C1 - C8-alkyl or aryl, each optionally substituted by halogen; or**

$R^1$  represents  $N=CR^6R^7$  wherein

$R^6$  represents a hydrogen atom, C1 - C6-alkyl or aryl, and

R<sup>7</sup> represents C1 - C6-alkyl or aryl, each optionally substituted by halogen; or

**R<sup>1</sup>** represents an isonitrile, isocyanate, isothiocyanate or a guanidino group; and  
**n** represents 0 or 1.

$n$  represents 0 or 1.

**In the specification and claims the term:**

**halogen has the meaning of Cl, Br, I or F;**

alkyl has the meaning of straight-chain or branched alkyl with 1 to 8, preferably 1 to 4 carbon atoms;

aryl has the meaning of aromatic, mono- or polycyclic hydrocarbon rings such as for example and preferred: naphthyl, anthranyl, phenanthryl, especially phenyl.

Preferred are compounds of formula I1 – I13 wherein

$R^1$  represents  $NR^2R^3$  wherein

**R<sup>2</sup>** represents a hydrogen atom or C1 - C4-alkyl and

$R^3$  represents  $C=OR^4$  wherein

$R^4$  represents a hydrogen atom or one of the groups  $OR^5$  or  $NHR^5$  wherein

$R^5$  represents C1 - C4-alkyl or aryl, each optionally substituted by halogen; or

5

$R^1$  represents  $N=CR^6R^7$  wherein

$R^6$  represents a hydrogen atom, methyl or optionally halogen substituted aryl, and

$R^7$  represents C1 - C4-alkyl or optionally halogen substituted aryl; or

10

$R^1$  represents an isonitrile, isocyanate, isothiocyanate or guanidino moiety.

Especially preferred are compounds of formula I1 - I13 wherein

$R^1$  represents  $NR^2R^3$  wherein

15  $R^2$  represents a hydrogen atom and

$R^3$  represents  $C=OR^4$  wherein

$R^4$  represents a hydrogen atom.

Especially preferred are also compounds of formula I1 - I13 wherein

20  $R^1$  represents  $NR^2R^3$  wherein

$R^2$  represents a hydrogen atom and

$R^3$  represents  $C=OR^4$  wherein

$R^4$  represents  $OR^5$  or  $NHR^5$  wherein

25  $R^5$  represents methyl, ethyl, n- or i-propyl or n-,s-,i- or t-butyl, or phenyl which is optionally substituted by halogen.

Especially preferred are also compounds of formula I1 - I13 wherein

$R^1$  represents  $N=CR^6R^7$  wherein

30  $R^6$  represents methyl, ethyl, n- or i-propyl, n-,s-,i- or t-butyl, or preferred a hydrogen atom or and

$R^7$  represents methyl, ethyl, n- or i-propyl, n-,s-,i- or t-butyl or phenyl.

Especially preferred are also compounds of formula I1 – I13 wherein  
R<sup>1</sup> represents an isonitrile, isocyanate, isothiocyanate or guanidino moiety.

5 Preferred are compounds wherein n represents 1.


Preferred are compounds of the formula I8

10 The aforementioned compounds are accessible by standard procedures of organic chemistry which can be adopted to the Rosin moiety. The starting Rosin derived from Tall Oil, Gum or Wood is commercially available; for example Rosin amine as Hercules® Amine D. An overview on the different isomers of abietic acid as well as their preparation is given by Gang-Fung Chen in *Progress in Organic Coatings* 20, 1992, 139-167. In the following general schemes the synthesis of the different Rosin  
15 amine derivatives is outlined. For reasons of simplification, the synthesis routes are outlined for substructure I8 with n = 1. The reaction sequences can be adopted easily to the other pure isomers and rosin oxidation/reduction products and also to mixtures of them.


#### 20 Scheme 1

Compounds of formula I8 are accessible via acylation of Rosin amine with a chloroformic-ester in an inert solvent with a base as HCl acceptor (see: Houben-Weyl Vol.8, 1952, 137-140; ibid. Vol.11/2, 1958, 27-37).



**Scheme 2**

- 5 Ureas of formula III can be synthesized by reacting Rosin amine with an isocyanate in an inert solvent (benzene, toluene, hydrocarbons etc.); see: Houben-Weyl Vol. E4, 1983, 352-357 or alternatively via reaction of Rosin isocyanate (s. below) with an aliphatic or aromatic amine.




10

**Scheme 3**

Schiff-bases of Rosin amine are accessible via condensation of Rosin amine with an aldehyde or keton (Houben-Weyl Vol. 11/2, 1958, 74-85).

15



The synthesis of Rosin isocyanide has been published (T. Ohsawa et al., Tetrahedron Lett., 1989, 845-846).

Rosin isothiocyante (CAS-Nr.: 115 269-93-7) can be synthesized from Rosin amine through reaction with thiophosgene (see analogous sequence with phosgene: Ozaki, Chem Rev. 72, 457-460), or alternatively with a thiophosgene substitute, namely thiocarbonyl-diimidazole (see example 3).

The preparation of Rosin isocyanate has been described (E. Corey et al., Tetrahedron Lett. 1981, 299-302).

In the case of compounds of formula 1 with  $n = 0$ , the required starting material Dehydroabietan-1-yl-amine can be obtained according to Stockel et al., Can.J.Chem. 1963, 834-836.

The synthesis of Dehydroabietan-1-yl-isocyanate is described in Chem.Pharm.Bull. 1985, 1472-1487.

All other derivatives (formula I,  $n=0$ ) can be synthesized in analogous manner as described for Rosin amine.

### Detailed Description of the Preferred Embodiment

A fouling organism which may be combatted or controlled by the method of the invention can be any marine or freshwater organism which can attach to an inner or outer surface of a structure which is submerged or in continual contact with water.

5 Exemplary organisms include algae, including members of the phyla Chlorophyta, Phaeophyta and Rhodophyta; tunicates, including members of the class Ascidiacea such as *Ciona intestinalis*, *Diplosoma listerianum* and *Botryllus sclosseri*, and members of the class Hydrozoa including *Clava squamata*, *Hydractinia echinata*, *Obelia geniculata* and *Tubularia larynx*;

10

Bivalves including *Mytilus edulis*, *Cassostrea virginica*, *Ostrea edulis*, *ostrea chilensis*, *Lasaea rubra* and members of the family Dreissenidae (or zebra mussels) and members of the family Corbuculidae (or Asiatic clams), bryozoans including *Electra pilosa*, *Conopeum reticulatum*, *Bugula neritina* and *Bowerbankia gracilis*;

15

Polychaete worms including *Hydroides norvegica*, *Pomatoceros triqueter*, *Mercierella enigmata* and *Spirorbis spp.*;

20

Sponges and members of the class Cirripedia (barnacles) such as *Balanus amphitrite*, *Lepas anatifera*, *Balanus balanus*, *Balanus balanoides*, *Balanus hameri*, *Balanus creatus*, *Balanus improvisus*, *Balanus galeatus*, *Balanus eburneus*, *Elminius modestus*, *Balanus tulipiformis* and *Balanus perforatus*.

25

Organisms of the genus *Balanus* are frequent foulers of aquatic structures. Specific fouling organisms to which this invention is especially directed include barnacles, zebra mussels, algae, diatoms, hydroids, bryozoa, ascidians, tube worms and asiatic clams, but also the bacterial slime.

30

Among the aquatic structures which may be protected by the method of invention are any submerged or partially submerged structure, either mobile or stationary, such as

a fishnet, boat, ship, piling, cooling tower, pipeline, standpipe, heat exchanger, dam, intake screen or the like.

In actual practice compound of formula I1 – I13 may be brought into contact with a fouling organism by:

- coating the aquatic structure to be protected with an antifouling-effective amount of said Rosin Amine derivative such that the antifouling compound is released at the to be protected surface area into the aquatic environment immediately.
- including an antifouling-effective amount of the Rosin Amine Derivative within material formed into an aquatic structure which then releases said compound,
- releasing an antifouling-effective amount of said compound directly into the aquatic environment surrounding the structure to be protected,
- or any other method wherein the Rosin Amine Derivative comes in contact with the fouling organism.

The amount of Rosin Amine Derivative to be used in the method of invention will vary according to the specific compound used, the identity of the fouling organism to be controlled, degree of fouling pressure of the surrounding aquatic environment, the water temperature, the mode of contact and the like.

The Rosinamine derivatives can be used as individual active compounds or else in combination with active compounds usually employed in the anti-fouling sector. These can preferably be heavy metals, such as Cu, or heavy metal compounds, such as, for example, bis(trialkyltin) sulphides, tri-n-butyl laurate, tri-n-butyl chloride, copper(I) oxide, triethyltin chloride, tri-n-butyl(2-phenyl-4-chlorophenoxy)-tin, tri-

butyltin oxide, molybdenum disulfide, antimony oxide, polymeric butyl titanate, phenyl-(bispyridine)-bismuth chloride, tri-n-butyltin fluoride, manganese ethylene-bisdithiocarbamate, zinc dimethyldithiocarbamate, zinc ethylenebisdithiocarbamate, the zinc salt or copper salt of 2-pyridinethiol-1-oxide, bisdimethyldithiocarbamoyl-  
5 zinc ethylenebisdithiocarbamate, zinc oxide, copper(I) ethylene-bis-dithiocarbamate, copper thiocyanate, copper naphthenate and tributyltin halides.

The action spectrum of the rosinamine derivatives is extended further or particular effects are achieved by these combinations of active compounds. Synergistic effects  
10 are obtained in many cases. The synergistic effect manifests itself particularly clearly if the active compound combinations are present in certain weight ratios. However, the weight ratios of the active compounds in the active compound combinations can vary within a relatively wide range.

15 Preferred combination partners for the rosinamine derivatives are algicides, such as diuron, dichlorophen, endothal, fentin acetate or quinoclamine, molluscicides, such as fentin acetate, metaldehyde, methiocarb, niclosamide, thiodicarb and trimethacarb, fungicides, such as dichlofluanid, tolylfluanid, iodopropargyl butylcarbamate, fluor-  
20 folpet and azoles, such as propiconazole, metconazole, cyproconazole and tebuconazole or conventional antifouling active compounds, such as 2-(N,N-dimethylthiocarbamoylthio)-5-nitrothiazyl, tetrabutyl-distannoxane, 2-tert-butylamino-4-cyclopropylamino-6-methylthio-1,3,5-triazine, 4,5-dichloro-2-n-octyl-4-isothiazolin-3-one, 2,4,5,6-tetrachloroisophthalodinitril, tetramethylthiuram disulphide, 2,4,6-trichlorophenylmaleimide, 2,3,5,6-tetrachloro-4-(methylsulphonyl)-pyridine, diiodomethyl-  
25 paratryl sulphone, thiabendazol, tetraphenyl-boron-pyridin salt, and the copper and sodium salt of 2-pyridinethiol-1-oxide.

The anti-fouling composition preferably comprises the rosinamine derivatives in concentrations of 0.5 to 60% by weight, preferably between 1 to 25% by weight.

Compositions of the invention comprise an aquatically acceptable inert carrier and an antifouling-effective amount of a Rosin Amine Derivative of formula I. For application onto structural surfaces, preferred compositions of the invention include a film-forming component such as a polymer resin solution. Exemplary polymer resins include unsaturated polyester resins formed from: a) unsaturated acids or anhydrides, such as maleic anhydride, fumaric acid, itaconic acid and the like; b) saturated acids or anhydrides, such as phthalic anhydride, isophthalic anhydride, terephthalic anhydride, tetrahydrophthalic anhydride, tetrahalophthalic anhydride, adipic acid, suberic acid, and the like; c) glycols, such as ethylene glycol, and the like; d) vinyl monomers, such as styrene, vinyl toluene, chlorostyrene, bromostyrene, acrylates like methylmethacrylate, ethylene glycol dimethacrylate and the like. Other suitable resins include vinyl ester-, vinyl acetate-, and vinyl chloride-based resins, elastomeric components, vulcanized rubbers, rosins, metalresinates and urethane-based resins.

For further description of components common in antifouling paints see Ungerer in Chem.Ind. 1985, 37, 730 – 732 and Williams in Antifouling Marine Coatings, Noyes, Park Ridge, 1973.

#### Example 1

##### N-Formyl-rosinamine ( 1 )

The starting material Rosinamine (Hercules® Amine D) is a mixture of primary amines derived from modified Rosin. It is described as dehydroabietylamine of technical grade and was used in the following syntheses without further purification.

To a solution of Rosin amine in ethyl acetate 5 equiv. of ethyl formate are added at room temperature under continuous stirring. After 16h at rt, the solvent is evaporated to dryness and the residue is filtered through a short column of silica gel to furnish N-formyl rosin amine under the form of a compact resin (yield: 86%).

Characterisation: visqueous oil; <sup>1</sup>H-NMR, δ(ppm): 7.94-8.23(1H); 7.15 (1H); 6.99 (1H); 6.89 (1H); 5.46 (1H); 2.76-3.27 (5H); 1.22 (6H); 1.21 (3H); 0.95 (3H).

**Example 2****Rosin isocyanide ( 2 )**

Diisopropylamine (2.7 equiv.) and phosphorous oxychloride (1.1equiv.) were successively added dropwise to a stirred solution of N-formyl rosinamine in dichloromethane at 0°C under an atmosphere of dry nitrogen. After 1h at 0°C, a 20% solution of sodium carbonate was added and the reaction mixture was allowed to reach room temperature for 1h. 20% sodium carbonate and water were added, extraction of the aqueous phase with dichloromethane followed by filtration of the residue through a column of silica gel furnished Rosin isocyanide as a colourless oil (yield: 85%).

Characterisation: visqueous oil; <sup>1</sup>H NMR, δ(ppm): 7.16 (1H); 7.00 (1H); 6.88 (1H); 2.76-3.34 (5H); 1.22 (6H); 1.21 (3H); 0.98 (3H).

**Example 3****Rosin isothiocyante ( 3 )**

A solution of thiocarbonyl diimidazole (1.5equiv.) in dichloromethane was added to a stirred solution of Rosinamine in dichloromethane at 0°C under an atmosphere of dry nitrogen. After the addition was complete, the reaction mixture was heated at 45°C during 16h. The solvent was evaporated and the solid residue filtered through a column of silica gel to furnish Rosinisothiocyante as an oil (yield: 87%).

Characterisation: oil; <sup>1</sup>H-NMR, δ(ppm): 7.16 (1H); 6.99 (1H); 6.89 (1H); 3.37 (2H); 2.90 (2H); 2.82 (1H); 1.22 (6H); 1.21 (3H); 0.96 (3H).

**Evaluation of Marine Antifouling Activity of Test Compounds**

The rate of settlement of laboratory reared cyprid larvae of the barnacle *Balanus amphitrite* was determined for testing the activity of candidate anti-fouling compounds.

**Settlement Assay**

Tests are carried out in four replicates in sterile polystyrene multi well plates. Between 25 and 40 cyprid larvae are injected in the dishes containing either 2ml of

test solution (see below), solvent control or a positive control (Dichloro-n-octylisothiazolinone).

5 Dishes are incubated for 24h at a temperature of  $27^{\circ}\text{C} \pm 2$ . After incubation the cyprids are screened for signs of toxicity. Larvae are classified in three categories: A) alive and swimming; B) alive but not active; C) dead. The test is terminated by addition of a drop of 20% formaldehyde and the numbers of settled and non-settled larvae are counted.

10 Settlement is evaluated as follows: 1) Non settled: not attached free swimming cyprids; 2) settled cyprids: attached, but not metamorphosed cyprids; 3) barnacles: attached juvenile barnacles.

15 Categories 2 and 3 are considered to be settled. Percentage settlement in test solution is compared with controls. Estimates of the *median effect concentration* (EC-50) after 50 hrs. are calculated using the Spearman-Kärber method.

20 All seawater used is of natural origin and filtered unto 0.2 micron. Stock solutions of test compounds are prepared by dissolving an amount of test substance in a suitable solvent and subsequent addition of seawater.

25 The stock solutions are used to prepare several dilution series in seawater. Controls are made of seawater, or, if appropriate, in a mixture of seawater and solvent. The solvent concentration in the controls is equal to the highest concentration in the test solution. As an internal standard (positive control) a concentration range of 0 to 5ppm dichloro-n-octylisothiazolinone will is included in each test.

### Test Results

30	Compound	EC50 for settlement inhibition in ppm
	1	2.6















- 15 -

2	0.12
---	------

reference*	0.37
------------	------

\*  $\equiv$  4,5-dichloro-n-octylisothiazolinone

**PATENT CLAIMS****1. Compounds of the formula I**

wherein

$R^1$  represents  $NR^2R^3$  wherein  
 $R^2$  represents a hydrogen atom, C1 - C8-alkyl and  
 $R^3$  represents  $C=OR^4$  wherein  
5  $R^4$  represents a hydrogen atom or one of the groups  $OR^5$  or  $NHR^5$  wherein  
 $R^5$  designates C1 - C8alkyl or aryl, each optionally substituted by halogen; or

10  $R^1$  represents  $N=CR^6R^7$  wherein  
 $R^6$  represents a hydrogen atom, C1 - C6-alkyl or aryl, and  
 $R^7$  represents C1 - C6-alkyl or aryl, each optionally substituted by halogen; or

15  $R^1$  represents an isonitril, isocyanate, isothiocyanate or guanidino group; and

$n$  represents 0 or 1.

2. Compounds of the formula I according to claim 1, wherein

20  $R^1$  represents  $NR^2R^3$  wherein  
 $R^2$  represents a hydrogen atom or C1 - C4-alkyl and  
 $R^3$  represents  $C=OR^4$  wherein  
 $R^4$  represents a hydrogen atom or one of the groups  $OR^5$  or  $NHR^5$  wherein  
25  $R^5$  represents C1 - C4-alkyl or aryl, each optionally substituted by halogen; or

30  $R^1$  represents  $N=CR^6R^7$  wherein  
 $R^6$  represents a hydrogen atom, methyl or optionally halogen substituted aryl, and

$R^7$  represents C1 - C4-alkyl or optionally halogen substituted aryl;  
or

$R^1$  represents an isonitrile, isocyanate, isothiocyanate or guanidino moiety.

3. Compounds of the formula I according to claim 1, wherein
  - $R^1$  represents  $NR^2R^3$  wherein
  - $R^2$  represents a hydrogen atom and
  - 10  $R^3$  represents  $C=OR^4$  wherein
  - $R^4$  represents a hydrogen atom.
4. Method for controlling or combatting a marine or freshwater fouling organism which comprises contacting said organism or the locus thereof with  
15 an anti-fouling-effective amount of at least one compound of formula I as defined in claim 1.
5. Agents, characterized in that they comprise an antifouling-effective amount of  
20 at least one compound of formula I as defined in claim 1 and an aquatically acceptable inert carrier.
6. Use of compounds of formula I or agents as defined in claims 1 and 3 to control and combat marine and/or freshwater fouling organism.
- 25 7. Process for the preparation of anti-fouling agents, characterized in that compounds of formula I as defined in claim 1 are mixed with an aquatically acceptable inert carrier.

# INTERNATIONAL SEARCH REPORT

In. tional Application No

PCT/EP 00/02118

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C07C233/02 C09D5/16 C07C331/24 C07C265/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C07C C09D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	BRIAN E CROSS ET AL: "Preparation of the 15,6alpha-Lactone from 8beta,13beta -Tetrahydroabiatic acid" JOURNAL OF THE CHEMICAL SOCIETY, PERKIN TRANSACTIONS 1, vol. 12, 1981, pages 3158-3160, XP002100081 page 3158	1,2
X	RANE D S ET AL: "NEW STRATEGIES FOR THE HOFMANN REACTION" JOURNAL OF CHEMICAL TECHNOLOGY AND BIOTECHNOLOGY (INTERNATIONAL JOURNAL OF BIOTECHNICAL AND CHEMICAL PROCESSES), vol. 59, no. 3, 1 March 1994 (1994-03-01), pages 271-277, XP000435976 page 272	1,2

-/-

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

3 May 2000

Date of mailing of the international search report

30/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Sánchez García, J.M.

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 00/02118

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 473 004 A (GOODYEAR TIRE & RUBBER) 4 March 1992 (1992-03-04) claims	1-7
A	EP 0 877 061 A (YOSHITOMI FINE CHEMICALS LTD) 11 November 1998 (1998-11-11) page 2 -page 28	1-7
A	WO 91 15546 A (COURTAULDS COATINGS HOLDINGS) 17 October 1991 (1991-10-17) page 7	4-7
A	EP 0 364 271 A (COURTAULDS COATINGS LTD) 18 April 1990 (1990-04-18) column 3	1-7

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/02118

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0473004 A	04-03-1992	US 5134184 A	28-07-1992
		BR 9103571 A	12-05-1992
		CA 2036672 A	28-02-1992
		DE 69117391 D	04-04-1996
		DE 69117391 T	19-09-1996
		JP 4233957 A	21-08-1992
EP 0877061 A	11-11-1998	NO 983388 A	25-09-1998
		CN 1214067 A	14-04-1999
		WO 9727254 A	31-07-1997
WO 9115546 A	17-10-1991	CN 1055940 A	06-11-1991
		DE 69106359 D	09-02-1995
		DE 69106359 T	22-06-1995
		DK 530205 T	06-06-1995
		EP 0530205 A	10-03-1993
		ES 2067228 T	16-03-1995
		GR 3015104 T	31-05-1995
		PT 97319 A, B	31-12-1991
EP 0364271 A	18-04-1990	AU 646754 B	03-03-1994
		AU 2092492 A	15-10-1992
		AU 624637 B	18-06-1992
		AU 4276089 A	26-04-1990
		AU 630114 B	22-10-1992
		AU 4276289 A	26-04-1990
		BR 8905149 A	15-05-1990
		BR 8905176 A	15-05-1990
		CA 2000495 A	13-04-1990
		CA 2000499 A	13-04-1990
		CN 1041771 A	02-05-1990
		CN 1041772 A	02-05-1990
		DE 68920688 D	02-03-1995
		DE 68920688 T	13-07-1995
		DE 68925290 D	08-02-1996
		DE 68925290 T	27-06-1996
		DK 87595 A	03-08-1995
		DK 506989 A	14-04-1990
		DK 507089 A	14-04-1990
		EP 0364272 A	18-04-1990
		EP 0529693 A	03-03-1993
		ES 2067553 T	01-04-1995
		ES 2081545 T	01-03-1996
		FI 953471 A	18-07-1995
		GR 3015105 T	31-05-1995
		GR 3018945 T	31-05-1996
		HK 1000670 A	17-04-1998
		JP 2151672 A	11-06-1990
		JP 2196869 A	03-08-1990
		KR 136283 B	24-04-1998
		MX 172244 B	09-12-1993
		MX 170259 B	12-08-1993
		NO 179413 B	24-06-1996
		NO 894080 A	17-04-1990
		NO 943208 A	17-04-1990
		PT 91982 A, B	30-04-1990
		PT 91983 A, B	30-04-1990
		US 5116407 A	26-05-1992

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/02118

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0364271 A		US 5236493 A CN 1088238 A,B	17-08-1993 22-06-1994